

PAC MASTER PLUS - Spécifications techniques



Description

PAC MASTER PLUS est un pneu diagonal pour compacteurs caractérisé par une zone de contact plus large qui offre une plus grande stabilité. Il est réalisé dans un mélange spécial qui lui confère une grande résistance à la chaleur. PAC MASTER PLUS assure un cycle de vie plus long du pneu.

UM

US Standard

Construction

 BIAS

Machinery

Industriel: Compacteur

Version	STANDARD
Type	TT
Tyre Size	7.50 - 15

Dimensions US Standard

Usa code	94048809
Ply Rating	14
Section Width (inch)	8.9
Overall Diameter (inch)	31.1
Static Loaded Radius (inch)	14.8
Rolling Circumference (inch)	93.9
Rim Rec	6.0
Rim Alt	6.5
ECE	E11-106R-005322

Load capacity (lbs)

mph / psi	127
5	6400
10	5070

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 15:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..