

PORTMAX PM 93 PLUS - Fiche de données



Description

PORTMAX PM 93 PLUS a été spécialement conçu pour les chariots cavaliers dans les opérations de manutention des conteneurs dans les ports. Le pneu radial All Steel (Tout Acier) avec ceintures en acier à plusieurs couches garantit une plus grande stabilité et une meilleure durabilité. Le mélange spécial antistatique de la bande de roulement assure une bonne résistance à la chaleur et un cycle de vie plus long du pneu. PORTMAX PM 93 PLUS offre une résistance réduite au roulement, ce qui permet des économies de carburant.

UM

International Standard

Construction

 RADIAL

Machinery

Industriel: Chariot cavalier

| SIZE | Version | Star R | LI/SS | RIM REC | RIM ALT | OW | OD | SLR | RC | Type |
|------------|------------|--------|--------|-----------|---------|-----|------|-----|------|------|
| 16.00 R 25 | INDUSTRIAL | ** | 200 A5 | 11.25/2.0 | | 425 | 1515 | 699 | 4582 | TL |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 11:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..