

POWER RIB F2 - Fiche de données



Description

POWER RIB F2 a été particulièrement conçu pour les tracteurs 2WD/2RM dans les applications de travail de la terre. Ce pneu, qui trouve son utilisation essentiellement aux champs, est parfait pour toutes les opérations qui demandent un excellent braquage.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Tracteur 2WD

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
11L - 15 SL	STANDARD	F2	110 A6	8	8 LB	10 LB	279	813	374	2423	TL	E11-106R-004652

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 12:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..