

## POWER TRAX HD (SS) - Spécifications techniques



### Description

Le pneu POWER TRAX HD premium est spécialement conçu pour les équipements dans les ports et les mines souterraines. Sa bande de roulement profonde, son côté extra-épais et sa carcasse résistante lui confèrent une durabilité exceptionnelle, minimisant les risques de crevaison et de dommages accidentels. Le pneu présente une excellente résistance aux coupures et aux éclats, ce qui le rend particulièrement adapté aux surfaces rugueuses et dures. Le protège-jante de conception spécifique assure une protection contre les crevaisons et les impacts et chocs au niveau du rebord de la jante.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industriel: Chargeur compact

Version	STANDARD
Type	TL
Tyre Size	12 - 16.5

## Dimensions International Standard

Ply Rating	14
Section Width (mm)	324
Overall Diameter (mm)	865
Static Loaded Radius (mm)	391
Rolling Circumference (mm)	2552
Rim Rec	9.75
ECE	E11-106R-005562

## Load capacity (Kg)

km/h / bar	6.20
10	3075
15	2430
25	2245

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 14:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..