

POWER TRAX HD - Spécifications techniques



Description

Le pneu POWER TRAX HD premium est spécialement conçu pour les équipements dans les ports et les mines souterraines. Sa bande de roulement profonde, son côté extra-épais et sa carcasse résistante lui confèrent une durabilité exceptionnelle, minimisant les risques de crevaison et de dommages accidentels. Le pneu présente une excellente résistance aux coupures et aux éclats, ce qui le rend particulièrement adapté aux surfaces rugueuses et dures. Le protège-jante de conception spécifique assure une protection contre les crevaisons et les impacts et chocs au niveau du rebord de la jante.

UM

International Standard

Construction

 BIAS

Machinery

Industriel: Chariot porte-conteneur
OTR: Véhicule miniers souterrains

Version	STANDARD
Type	TT
Tyre Size	12.00 - 20

Dimensions International Standard

Ply Rating	28
Section Width (mm)	320
Overall Diameter (mm)	1150
Rim Rec	8.50
Rim Alt	9.0

Load capacity (Kg)

	km/h / bar	10.00
25 LOAD WHEEL		9490
25 STEER WHEEL		7300
10 OTHER VEHICLES		9490
25 OTHER VEHICLES		7300
STATIC SIDE LOADER		11025

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 14:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..