

POWER TRAX - Spécifications techniques



Description

Le POWER TRAX est un pneu haut de gamme spécialement conçu pour le service à usage intensif sur remorque portuaire, chariot de conteneurs vides ou machines d'extraction minière ECH et souterraine. Sa bande de roulement profonde et sa carcasse robuste offrent une durabilité exceptionnelle, réduisant au minimum le risque de crevaison et de dommage accidentel. Le POWER TRAX est le pneu idéal pour les opérations lourdes et difficiles, grâce au composé de sa bande de roulement unique qui offre une excellente résistance aux coupures et aux déchirures.

UM

International Standard

Construction

 BIAS

Machinery

Industriel: Chariot porte-conteneurs vide
OTR: Véhicule miniers souterrains

Version	STANDARD
Type	TT
Tyre Size	12.00 - 20
LI/SS	176 A5

Dimensions International Standard

Ply Rating	20
Section Width (mm)	320
Overall Diameter (mm)	1150
Rim Rec	8.5
Rim Alt	9.0

Load capacity (Kg)

	km/h / bar	10.00
25 LOAD WHEEL		9230
25 STEER WHEEL		7100
10 OTHER VEHICLES		9230
25 OTHER VEHICLES		7100
STATIC SIDE LOADER		10720

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 01:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..