

## PRO RIB F2M - Spécifications techniques



### Description

PRO RIB F2M est un pneu agriculture pour les tracteurs 2WD/2RM dans les applications de travail de la terre. Ce pneu convient particulièrement pour toutes les opérations qui demandent un haut niveau de maniabilité.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Tracteur 2WD

Industriel: Remorque

Version	STANDARD
Type	TT
Tyre Size	10.00 - 16 SL
LI/SS	110 A8

## Dimensions International Standard

Ply Rating	8
Section Width (mm)	275
Overall Diameter (mm)	894
Static Loaded Radius (mm)	409
Rolling Circumference (mm)	2620
Rim Rec	8 LB
Rim Alt	W 8 L
ECE	E4-106R-002666
TRA Code	F2M

## Load capacity (Kg)

km/h / bar	3.00
40	1060

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 01:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..