

PUDDLE SPECIAL (A) - Fiche de données



Description

PUDDLE SPECIAL est un pneu pour l'agriculture R-2 particulièrement conçu pour les applications dans les rizières. Le dessin extra-profond de la bande de roulement, en plus de la disposition spéciale des pavés, assure une adhérence parfaite et une excellente traction même sur terrains meubles et mouillés. Le large élément central offre une meilleure capacité d'adaptation pour les applications sur route ainsi que d'excellentes performances opérationnelles. Qui plus est, PUDDLE SPECIAL bénéficie d'excellentes capacités d'auto-nettoyage et d'une durabilité élevée.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Tracteur

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
12.4 - 28	STANDARD	R2+	137 A2	12	W 11	W 10	325	1385	649	4067	TT	
11 - 32	STANDARD	R2+	111 A2	6	W 10	W 9	305	1465	702	4384	TT	E11-106R-004096
11 - 32	STANDARD	R2+	111 A2	6	W 10	W 9	305	1465	702	4384	TL	E11-106R-004096

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 12:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..