

RIB 900 - Spécifications techniques



Description

RIB 900 est un pneu adapté pour le transport, le travail de la terre et la récolte du foin avec remorques, outils agricoles et presses à balles de foin. Ce pneu offre une grande capacité de charge ainsi qu'un long cycle de vie.

UM

US Standard

Construction

❖ BIAS

Machinery

Agriculture: Presse à paille • Moissonneuse • Outillage agricole • Remorque

Version	STANDARD
Type	TL
Tyre Size	400/60 - 15.5
LI/SS FREE ROLLING	139 A8

Dimensions US Standard

Usa code	94026357
Ply Rating	10
Section Width (inch)	15.9
Overall Diameter (inch)	34.4
Static Loaded Radius (inch)	15
Rolling Circumference (inch)	100.9
Rim Rec	AG 13.00

Load capacity (lbs)

mph / psi	36
5 FR	6910
15 FR	5870
20 FR	5530
25 FR	4940

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 17:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..