

RIB 900 - Fiche de données



Description

RIB 900 est un pneu adapté pour le transport, le travail de la terre et la récolte du foin avec remorques, outils agricoles et presses à balles de foin. Ce pneu offre une grande capacité de charge ainsi qu'un long cycle de vie.

UM

International Standard

Construction

❖ BIAS

Machinery

Agriculture: Presse à paille • Moissonneuse • Outillage agricole • Remorque

SIZE	Version	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
400/60 - 15.5	STANDARD	139 A8	10	AG 13.00		405	875	380	2564	TL	
400/60 - 15.5	STANDARD	145 A8	14	AG 13.00		405	875	380	2564	TL	E4-106R-001551
400/60 - 15.5	STANDARD	147 A8	16	AG 13.00		405	875	380	2564	TL	E4-106R-001548

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 17:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..