

RIB TRAILER - Fiche de données



Description

RIB TRAILER est un pneu bias (à structure diagonale) spécialement conçu pour les utilisations sur route et hors route avec des machines agricoles, tout particulièrement les moissonneuses-batteuses. Sa conception à 4 nervures optimise la répartition de la charge, et sa carcasse solide assure la résistance aux chaumes. RIB TRAILER a été conçu avec un composé spécial qui garantit une excellente durée de vie au pneu grâce à sa grande résistance à l'usure.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Outillage agricole

SIZE	Version	LI/SS	PR	RIM REC	RIM ALT	SW	OD	Type
6.00 - 16	STANDARD	94 A6	8	4.50 E	4.00 E ; 5 K ; 5.00 F	170	735	TT
7.00 - 19	STANDARD	119 A3	10	5.00		210	875	TT

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 12:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..