

RIDEMAX FL 693 M - Spécifications techniques



Description

RIDEMAX FL 693 M est le pneu idéal pour les applications de transports fréquents sur route avec des remorques/camions-citernes. Conçu pour l'utilisation 75% sur route, RIDEMAX FL 693 M présente des prestations excellentes sur route et priorise aussi le confort et les propriétés d'auto-nettoyage. L'indice de vitesse classe D/E de la gamme est synonyme de vitesse élevée sur la route avec un gain de temps considérable. La résistance au roulement réduite contribue à l'économie de carburant, tandis que la tringle renforcée et les ceintures en acier assurent une durabilité avancée.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Véhicule citerne • Remorque

Version	STANDARD
Type	TL
Tyre Size	VF 400/45 R 17.5
LI/SS	142 D

Dimensions International Standard

Section Width (mm)	400
Overall Diameter (mm)	800
Static Loaded Radius (mm)	357
Rolling Circumference (mm)	2448
SRI (mm)	390
Rim Rec	14.00
ECE	E11-106R-007199

Load capacity (Kg)

km/h / bar	1.2	1.6	2	2.4	2.8	3.2	3.6	4.0
70	1040	1260	1405	1620	1840	2005	2200	2415
65	1140	1380	1540	1780	2015	2200	2415	2650
50	1385	1670	1865	2155	2440	2665	2925	3210
40	1555	1875	2095	2420	2740	2995	3285	3605
30	1725	2085	2325	2685	3045	3325	3645	4005
25	1805	2180	2435	2810	3185	3480	3815	4190
10	2055	2485	2770	3200	3630	3960	4345	4770

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 20:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..