

RIDEMAX FL 699 - Spécifications techniques



Description

RIDEMAX FL 699 est le pneu BKT idéal pour les applications sur route avec remorques et camions-citernes. Ce pneu All Steel se distingue de par le kilométrage élevé et la durabilité. La tringle renforcée garantit une meilleure stabilité même à des vitesses élevées. Même si ce pneu radial a été conçu pour une utilisation sur route à 90%, c'est-à-dire pour le transport dans les applications agricoles, le nouveau RIDEMAX FL 699 offre aussi d'excellentes performances aux champs. Lors de la conception du pneu, une attention particulière a été accordée à la capacité de charge afin de réduire le nombre de cycles de transport. Bonne nouvelle aussi pour les agriculteurs qui savent combien une remorque peut compromettre la conduite : RIDEMAX FL 699 offre un confort extraordinaire en assurant une conduite sûre et un bon contrôle du véhicule.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Véhicule citerne • Remorque

Version	STANDARD
Type	TL
Tyre Size	24 R 20.5
LI/SS	176 F

Dimensions US Standard

Usa code	94063680
Ply Rating	16
Overall Width (inch)	23.2
Overall Diameter (inch)	53.9
Static Loaded Radius (inch)	24.1
Rolling Circumference (inch)	164
Rim Rec	18.00
ECE	E11-54R-0017755

Load capacity (lbs)

mph / psi	58	73	87
25-30	11900	14220	16450
35-50	11330	13540	15660

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 01:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..