

RM 500 - Spécifications techniques



Description

RM 500 est un pneu radial avec ceintures d'acier, adapté pour les applications de récolte avec outillage agricole. Le pneu est équipé d'une carcasse robuste et un dessin particulier de la bande de roulement qui offrent une capacité de charge élevée en même temps qu'une excellente résistance aux coupures et lacérations. Grâce à son empreinte large, RM 500 assure une excellente répartition de la pression sur le terrain avec un compactage réduit du sol, en plus d'une traction exceptionnelle.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Moissonneuse

Version	STEEL BELTED
Type	TL
Tyre Size	600/65 R 28
LI/SS	177A8/165A8
LI/SS DRIVE WHEEL	165 A8
LI/SS FREE ROLLING	177 A8

Dimensions International Standard

Section Width (mm)	590
Overall Diameter (mm)	1486
Static Loaded Radius (mm)	640
Rolling Circumference (mm)	4340
SRI (mm)	700
Rim Rec	W 18 L
Rim Alt	W 20 L
ECE	E11-106R-007699

Load capacity (Kg)

km/h / bar	0.8	1.0	1.2	1.6	2.0	2.4	2.8
40 Free Rolling	3070	3505	3945	4820	5550	6425	7300
40 Drive Wheel	2165	2475	2785	3400	3915	4535	5150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 13:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..