

ROCK GRIP E4 - Fiche de données



Description

ROCK GRIP (E-4) est un pneu à construction diagonale particulièrement conçu pour les camions utilisés dans les opérations à l'intérieur des mines ou carrières. Chaque fois que vos conditions de travail pour les transports courts sur le site nécessitent à la fois résistance à la chaleur et protection contre les coupures, ROCK GRIP est le pneu qu'il vous faut.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Tombereau rigide

| SIZE | Version | USACode | TRA Code | PR | RIM REC | RIM ALT | OW | OD | SLR | RC | Type |
|------------|------------------------|----------|----------|----|-----------|-----------|------|-------|------|-------|------|
| 14.00 - 25 | STANDARD | 94042210 | E4 | 32 | 10.00/2.0 | | 14.8 | 55.5 | 25.6 | 164.3 | TL |
| 14.00 - 25 | STANDARD | 94041879 | E4 | 24 | 10.00/2.0 | | 14.8 | 55.5 | 25.6 | 164.3 | TL |
| 14.00 - 25 | STANDARD | 94039746 | E4 | 28 | 10.00/1.5 | | 14.8 | 55.5 | 25.6 | 164.3 | TL |
| 14.00 - 25 | STANDARD | 94039753 | E4 | 28 | 10.00/1.5 | | 14.8 | 55.5 | 25.6 | 164.3 | TT |
| 14.00 - 25 | STANDARD | 94041893 | E4 | 28 | 10.00/2.0 | | 14.8 | 55.5 | 25.6 | 164.3 | TL |
| 14.00 - 25 | STANDARD | 94042203 | E4 | 28 | 10.00/2.0 | | 14.8 | 55.5 | 25.6 | 164.3 | TT |
| 14.00 - 25 | STANDARD | 94039760 | E4 | 32 | 10.00/1.5 | | 14.8 | 55.5 | 25.6 | 164.3 | TL |
| 14.00 - 25 | STANDARD | 94039722 | E4 | 24 | 10.00/1.5 | | 14.8 | 55.5 | 25.6 | 164.3 | TL |
| 14.00 - 25 | STANDARD | 94041886 | E4 | 24 | 10.00/2.0 | | 14.8 | 55.5 | 25.6 | 164.3 | TT |
| 14.00 - 25 | STANDARD | 94039739 | E4 | 24 | 10.00/1.5 | | 14.8 | 55.5 | 25.6 | 164.3 | TT |
| 16.00 - 25 | STANDARD | 94027651 | E4 | 28 | 11.25/2.0 | 13.00/2.0 | 18.5 | 60 | 27.5 | 177.7 | TL |
| 16.00 - 25 | STANDARD | 94025879 | E4 | 32 | 11.25/2.0 | 13.00/2.0 | 18.5 | 60 | 27.5 | 177.7 | TL |
| 18.00 - 25 | STANDARD | 94015528 | E4 | 40 | 13.00/2.5 | 15.00/2.5 | 20.1 | 65 | 29.6 | 192.3 | TL |
| 18.00 - 25 | STANDARD | 94015498 | E4 | 32 | 13.00/2.5 | 15.00/2.5 | 20.1 | 65 | 29.6 | 192.3 | TL |
| 18.00 - 25 | STANDARD | 94015504 | E4 | 36 | 13.00/2.5 | 15.00/2.5 | 20.1 | 65 | 29.6 | 192.3 | TL |
| 18.00 - 25 | STANDARD | 94015511 | E4 | 40 | 13.00/2.5 | 15.00/2.5 | 20.1 | 65 | 29.6 | 192.3 | TT |
| 18.00 - 25 | STANDARD | 94015474 | E4 | 24 | 13.00/2.5 | 15.00/2.5 | 20.1 | 65 | 29.6 | 192.3 | TT |
| 18.00 - 25 | STANDARD | 94015481 | E4 | 32 | 13.00/2.5 | 15.00/2.5 | 20.1 | 65 | 29.6 | 192.3 | TT |
| 18.00 - 33 | CUT RESISTANT COMPOUND | 94048762 | E4 | 40 | 13.00/2.5 | | 20.1 | 74.3 | 34.2 | 219.9 | TL |
| 18.00 - 33 | CUT RESISTANT COMPOUND | 94048465 | E4 | 36 | 13.00/2.5 | | 20.1 | 74.3 | 34.2 | 219.9 | TL |
| 18.00 - 33 | STANDARD | 94015535 | E4 | 36 | 13.00/2.5 | | 20.1 | 74.3 | 34.2 | 219.9 | TT |
| 18.00 - 33 | STANDARD | 94015542 | E4 | 36 | 13.00/2.5 | | 20.1 | 74.3 | 34.2 | 219.9 | TL |
| 18.00 - 33 | STANDARD | 94015559 | E4 | 40 | 13.00/2.5 | | 20.1 | 74.3 | 34.2 | 219.9 | TT |
| 18.00 - 33 | STANDARD | 94015566 | E4 | 40 | 13.00/2.5 | | 20.1 | 74.3 | 34.2 | 219.9 | TL |
| 18.00 - 33 | STANDARD | 94015573 | E4 | 44 | 13.00/2.5 | | 20.1 | 74.3 | 34.2 | 219.9 | TL |
| 21.00 - 35 | CUT RESISTANT COMPOUND | 94048779 | E4 | 40 | 15.00/3.0 | | 22.8 | 80.3 | 37.1 | 238.9 | TL |
| 21.00 - 35 | CUT RESISTANT COMPOUND | 94067343 | E4 | 36 | 15.00/3.0 | | 22.8 | 80.3 | 37.1 | 238.9 | TL |
| 21.00 - 35 | STANDARD | 94015580 | E4 | 36 | 15.00/3.0 | | 22.8 | 80.3 | 37.1 | 238.9 | TL |
| 21.00 - 35 | STANDARD | 94015597 | E4 | 40 | 15.00/3.0 | | 22.8 | 80.3 | 37.1 | 238.9 | TL |
| 24.00 - 35 | CUT RESISTANT COMPOUND | 94044702 | E4 | 48 | 17.00/3.5 | | 25.8 | 86.2 | 39.5 | 255.2 | TL |
| 24.00 - 35 | STANDARD | 94015603 | E4 | 48 | 17.00/3.5 | | 25.8 | 86.2 | 39.5 | 255.2 | TL |
| 24.00 - 49 | CUT RESISTANT COMPOUND | 94048496 | E4 | 48 | 17.00/3.5 | | 25.8 | 99.6 | 46.6 | 295.2 | TL |
| 24.00 - 49 | STANDARD | 94026548 | E4 | 42 | 17.00/3.5 | | 25.8 | 99.6 | 46.6 | 295.2 | TL |
| 24.00 - 49 | STANDARD | 94025893 | E4 | 48 | 17.00/3.5 | | 25.8 | 99.6 | 46.6 | 295.2 | TL |
| 27.00 - 49 | CUT RESISTANT COMPOUND | 94044597 | E4 | 48 | 19.50/4.0 | | 29.1 | 106.1 | 49.3 | 314.4 | TL |
| 27.00 - 49 | CUT RESISTANT COMPOUND | 94067299 | E4 | 54 | 19.50/4.0 | | 29.1 | 106.1 | 49.3 | 314.4 | TL |
| 27.00 - 49 | STANDARD | 94035281 | E4 | 54 | 19.50/4.0 | | 29.1 | 106.1 | 49.3 | 314.4 | TL |
| 27.00 - 49 | STANDARD | 94026555 | E4 | 48 | 19.50/4.0 | | 29.1 | 106.1 | 49.3 | 314.4 | TL |
| 30.00 - 51 | CUT RESISTANT COMPOUND | 94044603 | E4 | 52 | 22.00/4.5 | | 32.7 | 114.6 | 53.1 | 339.2 | TL |
| 30.00 - 51 | STANDARD | 94029228 | E4 | 46 | 22.00/4.5 | | 32.7 | 114.6 | 53.1 | 339.2 | TL |
| 30.00 - 51 | STANDARD | 94029235 | E4 | 52 | 22.00/4.5 | | 32.7 | 114.6 | 53.1 | 339.2 | TL |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and

pressure condition.

Printed on 05/11/2024 11:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..