

## ROCK GRIP (T) - Spécifications techniques



### Description

ROCK GRIP (E-4) est idéal pour les tombereaux automoteurs dans les applications de carrières et les transports courts avec charges lourdes dans les mines. Le mélange spécial de la bande de roulement réduit au minimum les coupures et crevaisons même sur les terrains les plus difficiles. ROCK GRIP (E-4) offre une traction exceptionnelle ainsi qu'un long cycle de vie.

### UM

US Standard

### Construction

 BIAS

### Machinery

OTR: Camion à benne basculante • Tombereau rigide

Version	STANDARD
Type	TT
Tyre Size	12.00 - 24

## Dimensions US Standard

Usa code	94035755
Ply Rating	20
Overall Width (inch)	12.4
Overall Diameter (inch)	49.8
Static Loaded Radius (inch)	23.4
Rolling Circumference (inch)	147.8
Rim Rec	8.5
Rim Alt	8.0

## Load capacity (lbs)

mph / psi	115
50 LS/LD	8540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 23:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..