

RT 747 AGRO INDUSTRIAL - Spécifications techniques



Description

RT 747 AGRO INDUSTRIAL est un pneu radial agro-industriel adapté pour les chargeuses compactes et les chargeurs télescopiques. Les crampons extra larges assurent une excellente adhérence et une extraordinaire stabilité lors des opérations de levage. Le pneu a été développé avec un mélange résistant aux coupures et déchirures qui permet au pneu de supporter des charges lourdes. RT 747 AGRO INDUSTRIAL est la solution appropriée pour toutes les opérations agricoles en général qui demandent une grande polyvalence.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Chargeuse compacte • Chargeuse télescopique

Industriel: Chargeuse compacte • Chargeuse télescopique

| | |
|-----------|-----------------------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 460/70 R 24 (17.5L R 24) |
| LI/SS | 159A8/156B |

Dimensions US Standard

| | |
|------------------------------|-------------------|
| Usa code | 94059270 |
| Section Width (inch) | 18.3 |
| Overall Diameter (inch) | 49.4 |
| Static Loaded Radius (inch) | 21.9 |
| Rolling Circumference (inch) | 151.2 |
| Rim Rec | DW 15 L |
| Rim Alt | DW 14 L ; DW 16 L |
| ECE | E11-106R-005105 |

Load capacity (lbs)

| mph / psi | 17 | 23 | 29 | 35 | 41 | 46 | 51 | 58 |
|-----------|------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 3380 | 4170 | 4950 | 5640 | 6430 | 7200 | 7730 | 8820 |
| 25 | 3760 | 4630 | 5500 | 6270 | 7140 | 8000 | 8590 | 9640 |
| 20 | 3910 | 4820 | 5720 | 6530 | 7430 | 8320 | 8930 | 10030 |
| 15 | 3980 | 4910 | 5830 | 6650 | 7570 | 8490 | 9100 | 10230 |
| 5 Cyc | 5640 | 6940 | 8260 | 9410 | 10710 | 12000 | 12890 | 14470 |
| Static | 8640 | 10650 | 12650 | 14430 | 16420 | 18410 | 19750 | 22190 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 14:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..