

RT 851 - Fiche de données



Description

RT 851 est un pneu R-1 particulièrement conçu pour les tracteurs dans les applications sur pelouses. Le dessin spécial arrondi des crampons a été développé pour limiter tout éventuel dommage à la pelouse et aux plantes qui poussent, en modérant aussi le compactage du sol. La robuste carcasse en nylon avec ceintures résistantes en polyester garantit une traction exceptionnelle et une capacité de charge augmentée.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tracteur

SIZE	Version	USACode	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
14.9L R 20 (375/75 R 20)	STANDARD	94048632	R1	119 A8/B	W 13	W 11; W 12; W 14	14.9	43.3	19.6	129.4	TL	E11-106R-002989

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 12:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..