

## RT 857 - Spécifications techniques



### Description

RT 857 est un pneu qui convient pour les applications de travail de la terre. La carcasse robuste garantit une durabilité et une traction excellentes. Le mélange de la bande de roulement est caractérisé par une résistance élevée à tout type de coupure.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Tracteur

Version	STANDARD
Type	TL
Tyre Size	420/85 R 26 (16.9 R 26)
LI/SS	138 A8/B

## Dimensions International Standard

Section Width (mm)	450
Overall Diameter (mm)	1374
Static Loaded Radius (mm)	616
Rolling Circumference (mm)	4115
SRI (mm)	650
Rim Rec	DW 15 L
Rim Alt	W 14 L ; W 15 L ; W 16 L ; DW 16 L
ECE	E11-106R-003471
TRA Code	R1

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	1300	1515	1725	1940	2150	2360
40	1300	1515	1725	1940	2150	2360
30	1395	1620	1850	2075	2305	2530
10 LT	1745	2030	2315	2600	2885	3165
10 HT	1395	1620	1850	2075	2305	2530

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 17:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..