

## SKID POWER PLUS - Fiche de données



### Description

SKID POWER PLUS a été conçu pour les chargeuses compactes dans les applications du bâtiment. Les barrettes plus larges garantissent une excellente traction ainsi que des propriétés d'autonettoyage exceptionnelles. Ce pneu se distingue de par la bande de roulement extra-profonde et par une meilleure protection des flancs, ce qui assure une excellente résistance aux coupures et déchirures ainsi qu'une extraordinaire durabilité. SKID POWER PLUS est le pneu idéal pour les surfaces terreuses. La large zone de contact assure une stabilité optimale pendant les opérations.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industriel: Chargeur compact

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	Type
10 - 16.5	SPECIAL	94057412	10	8.25		9.9	30.5	TL
10 - 16.5	STANDARD	94054824	10	8.25		9.9	30.5	TL
10 - 16.5	STANDARD	94054664	8	8.25		9.9	30.5	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 11:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..