

## SKID POWER SK - Fiche de données



### Description

SKID POWER SK a été particulièrement conçu pour les chargeuses compactes dans les applications du secteur bâtiment. Les bourrelets de protection du flanc et de la jante associés à la bande de roulement extra profonde permettent au pneu d'avoir un long cycle de vie.

### UM

US Standard

### Construction

BIAS

### Machinery

Industriel: Chargeur compact

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
10 - 16.5	STANDARD	94017225		10	8.25		10.6	30.5	14	90	TL	
10 - 16.5	STANDARD	94017201		8	8.25		10.6	30.5	14	90	TL	
10 - 16.5	STANDARD	94047109	138 A2	12	8.25		10.6	30.5	14	90	TL	
10 - 16.5	IMPLEMENT	94055708	116 A8	8	8.25		10.6	30.5	14	90	TL	E11-106R-003543
10 - 16.5	IMPLEMENT	94055715	120 A8	10	8.25		10.6	30.5	14	90	TL	E11-106R-003544
12 - 16.5	IMPLEMENT	94055746	130 A8	12	9.75		12.3	32.5	14.8	95.8	TL	E11-106R-003568
12 - 16.5	IMPLEMENT	94055722	125 A8	10	9.75		12.3	32.5	14.8	95.8	TL	E11-106R-003545
12 - 16.5	STANDARD	94017249		10	9.75		12.3	32.5	14.8	95.8	TL	
12 - 16.5	STANDARD	94017263		12	9.75		12.3	32.5	14.8	95.8	TL	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 14:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..