



SM 54 M IND-4S - Spécifications techniques



Description

SM 54 M IND-4S est la version modifiée du SM 54. La bande de roulement plus plat lui confère un zone de contact plus large qui assure un cycle de vie plus long. Le pneu a été particulièrement conçu pour les machines de manutention de conteneurs vides et pour les reach stackers dans les applications intermodales/logistiques. SM 54 M se distingue de par une grande stabilité en mode levage ainsi que par un dessin profond et lisse de la bande de roulement, qui confère une excellente résistance aux coupures.

UM

US Standard

Construction

❖ BIAS

Machinery

Industriel: Reach stacker

Version	PORT INDUSTRIAL
Type	TL
Tyre Size	18.00 - 25

Dimensions US Standard

Usa code	94055791
Ply Rating	40
Overall Width (inch)	20.8
Overall Diameter (inch)	65
Static Loaded Radius (inch)	29.5
Rolling Circumference (inch)	192.1
Rim Rec	13.00/2.5
Rim Alt	15.00/2.5
TRA Code	IND-4S

Load capacity (lbs)

mph / psi	145
5	50600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 23:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..