

ST 180 - Spécifications techniques



Description

ST 180 est un pneu essentiellement utilisé sur la route, conçu pour les applications de transport avec remorques et outils agricoles. Le dessin spécifique de la bande de roulement réduit l'usure, garantissant un long cycle de vie du pneu. ST 180 est disponible en plus versions: une version « aramid belted », avec ceintures en aramide, pour donner une plus grande résistance aux perforations, tandis que la version spécial « special » assure une résistance élevée aux coupures et déchirures.

UM

US Standard

Construction

❖ BIAS

Machinery

Agriculture: Outillage agricole • Remorque

| | |
|-----------|----------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 6.00 - 9 |

Dimensions US Standard

| | |
|-------------------------|---------------------------------|
| Usa code | 94008827 |
| Ply Rating | 8 |
| Section Width (inch) | 6.5 |
| Overall Diameter (inch) | 21.3 |
| Rim Rec | 4.00 - I - 55 |
| Rim Alt | 4.50 - I - 55 ; I - 70 ; I - 90 |
| ECE | E4-54R-0022804 |

Load capacity (lbs)

| mph / psi | 85 |
|-----------|------|
| 62 | 1390 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 13:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..