

STEER FARM - Fiche de données



Description

STEER FARM a été conçu pour les tracteurs 2WD/2RM dans les applications de travail de la terre et il assure un excellent braquage.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Tracteur 2WD

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
5.20 - 14	STANDARD	F2	75 A6	6	3.50 D	4.00 E	135	625	296	1837	TT	E11-106R-004092
6.00 - 16	STANDARD	F2	94 A6	8	4.50 E	4.00 E ; 5 K ; 5.00 F	170	740	353	2279	TT	E4-106R-002186
6.50 - 16	STANDARD	F2	98 A6	8	4.50 E	4.00 E ; 5.00 F ; 5.50 F	185	770	0	0	TT	E4-106R-002187
7.50 - 16	STANDARD	F2	103 A6	8	5.50 F	5.00 F ; 5 K ; 6.00 F	205	805	378	2451	TT	E11-106R-003547
7.50 - 16	STANDARD	F2	109 A6	10	5.50 F	5.00 F ; 5 K ; 6.00 F	205	805	378	2451	TT	
6.50 - 20	STANDARD	F2	101 A6	8	5.50 F	4.00 E ; 5.00 F	196	878	418	2701	TT	E4-106R-002833

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 12:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..