

STEER GRIP - Spécifications techniques



Description

STEER GRIP est l'équipement idéal pour les essieux directeurs de tombereaux automoteurs. La large nervure centrale avec crampons linéaires rend le pneu bien adapté pour les applications FRT (pneus pour essieux tirés), garantissant d'excellentes performances tant en conditions mouillées que sèches hors route. Le mélange spécial de la bande de roulement a été réalisé pour donner une excellente résistance tant à l'usure qu'aux coupures et lacérations, tandis que la carcasse robuste assure un long cycle de vie du pneu.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Camion à benne basculante

Version	STANDARD
Type	TT
Tyre Size	12.00 - 24

Dimensions US Standard

Usa code	94049363
Ply Rating	20
Overall Width (inch)	12.2
Overall Diameter (inch)	49.1
Static Loaded Radius (inch)	23.1
Rolling Circumference (inch)	149
Rim Rec	8.5
Rim Alt	8.0

Load capacity (lbs)

mph / psi	115
50 LS/LD	8540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 13:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..