

## SUPER GRADER - Spécifications techniques



### Description

SUPER GRADER (G-2) est un pneu diagonal particulièrement conçu pour les niveleuses, qui fait preuve d'une excellente traction et d'une grande capacité d'auto-nettoyage. SUPER GRADER a été réalisé dans un mélange spécial qui permet d'avoir un cycle de vie plus long du pneu et d'être utilisé pour des services pénibles.

### UM

International Standard

### Construction

 BIAS

### Machinery

OTR: Niveleuse

Version	STANDARD
Type	TL
Tyre Size	13.00 - 24

## Dimensions International Standard

Ply Rating	12
Overall Width (mm)	340
Overall Diameter (mm)	1275
Static Loaded Radius (mm)	588
Rolling Circumference (mm)	3800
Rim Rec	8.00 TG SDC
Rim Alt	9.00/1.5 (DC) ; 10.00/VA SDC
TRA Code	G2

## Load capacity (Kg)

km/h / bar	3.00
40	2725

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 13:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..