

## SUPER SAND - Spécifications techniques



### Description

SUPER SAND est particulièrement adapté pour les remorques qui opèrent sur des surfaces sableuses dans des conditions climatiques de chaleur. Ce pneu se distingue de par une grande capacité de flottaison et il est idéal pour toutes les opérations qui demandent un niveau de maniabilité élevé.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industriel: Remorque

Version	STANDARD
Type	TT
Tyre Size	14.00 - 20

## Dimensions US Standard

Usa code	94028504
Ply Rating	18
Section Width (inch)	15.2
Overall Diameter (inch)	48.2
Rim Rec	10.00 V
Rim Alt	10.00 W

## Load capacity (lbs)

mph / psi	85
40 LS	8740
40 LD	7695

Printed on 04/07/2024 21:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..