

SUPER SAND - Fiche de données



Description

SUPER SAND est particulièrement adapté pour les remorques qui opèrent sur des surfaces sableuses dans des conditions climatiques de chaleur. Ce pneu se distingue de par une grande capacité de flottaison et il est idéal pour toutes les opérations qui demandent un niveau de maniabilité élevé.

UM

International Standard

Construction

BIAS

Machinery

Industriel: Remorque

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	Type
9.00 - 15	STANDARD	6	7.00		275	854	TT
9.00 - 16	STANDARD	8	6.50 H	6.00 G	255	885	TT
14.00 - 20	STANDARD	12	10.00 V	10.00 W	385	1225	TT
14.00 - 20	STANDARD	16	10.00 V	10.00 W	385	1225	TT
14.00 - 20	STANDARD	18	10.00 V	10.00 W	385	1225	TT
16.00 - 20	STANDARD	16	10.00 W		415	1305	TT

Printed on 04/07/2024 21:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..