

TF 8181 - Spécifications techniques



Description

TF 8181 est un pneu pour une utilisation aux champs et sur route conçu pour les tracteurs 2WD/2RM dans les applications de travail de la terre et de transport. Ce pneu assure un excellent niveau de braquage.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Tracteur 2WD

Industriel: Remorque

Version	SPECIAL
Type	TT
Tyre Size	5.50 - 16
LI/SS	86 A6

Dimensions International Standard

Ply Rating	6
Section Width (mm)	158
Overall Diameter (mm)	720
Static Loaded Radius (mm)	340
Rolling Circumference (mm)	2145
Rim Rec	4.00 E
Rim Alt	3.50 D ; 4.50 E
TRA Code	F2

Load capacity (Kg)

km/h / bar	3.70
30	530

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 02:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..