

TF 9090 - Spécifications techniques



Description

TF 9090 est un pneu conçu pour les micro tracteurs dans les opérations de travail de la terre. Le dessin spécial de la bande de roulement offre un excellent braquage sur le sol meuble.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Micro tracteur
Industriel: Remorque

Version	STANDARD
Type	TT
Tyre Size	7.50 - 20
LI/SS	105 A8

Dimensions US Standard

Usa code	94021260
Ply Rating	8
Section Width (inch)	8.1
Overall Diameter (inch)	36
Static Loaded Radius (inch)	17
Rolling Circumference (inch)	107.3
Rim Rec	5.50 F
Rim Alt	5.00 F
ECE	E4-106R-002710
TRA Code	F2

Load capacity (lbs)

mph / psi	56
25	2040

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 18:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..