

## TR 117 - Spécifications techniques



### Description

TR 117 est idéal pour les applications d'irrigation avec pivot central. Le dessin spécial de la bande de roulement lui confère une excellente traction en même temps que d'excellentes propriétés d'auto-nettoyage.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Arroseur à pivot

Version	STANDARD
Type	TL
Tyre Size	11.2 - 38
LI/SS	113 A8

## Dimensions US Standard

Usa code	94031368
Ply Rating	6
Section Width (inch)	11.2
Overall Diameter (inch)	56.9
Static Loaded Radius (inch)	26.6
Rolling Circumference (inch)	173.2
Rim Rec	W 10
Rim Alt	W 9
ECE	E4-106R-002748
TRA Code	R1

## Load capacity (lbs)

mph / psi	26	34
25	2540	---
CREEP	---	5345

\* - CREEP SPEED - 200 FT/30 MIN ( 61 M/30 MIN )

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 00:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..