

TR 135 - Spécifications techniques



Description

TR 135 est tout à fait adapté pour les tracteurs dans les applications de travail de la terre. La carcasse renforcée et le mélange particulièrement résistant aux coupures et déchirures garantit un cycle de vie du pneu plus long. D'excellentes performances en termes de traction, propriétés d'auto-nettoyage et capacité de charge sont les atouts qui font de TR 135 le pneu idéal même dans les conditions de terrain les plus critiques.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Tracteur
Industriel: Remorque

Version	DUAL BEAD HD
Type	TL
Tyre Size	20.8 - 42
LI/SS	164 A8

Dimensions US Standard

Usa code	94062751
Ply Rating	18
Section Width (inch)	21.1
Overall Diameter (inch)	76.8
Static Loaded Radius (inch)	35.8
Rolling Circumference (inch)	225.7
Rim Rec	W 18 L
Rim Alt	W 16 L
ECE	E11-106R-005853
TRA Code	R1

Load capacity (lbs)

mph / psi	46
25	11000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 16:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..