

## TR 136 - Spécifications techniques



### Description

TR 136 a été conçu par BKT pour être utilisé sur les tracteurs et remorques dans les opérations de travail de la terre et de transport. Ce pneu assure une traction supérieure dans toutes les conditions opérationnelles en même temps qu'une résistance optimale aux coupures et déchirures, réduisant ainsi les temps d'arrêt machine et augmentant donc votre productivité. Grâce au nombre plus élevé des revés, TR 136 assure une excellente traction même avec des charges élevés.

### UM

International Standard

### Construction

❖ BIAS

### Machinery

Agriculture: Tracteur • Remorque

|           |           |
|-----------|-----------|
| Version   | STANDARD  |
| Type      | TT        |
| Tyre Size | 12.4 - 28 |
| LI/SS     | 123 A6    |

## Dimensions International Standard

|                            |                 |
|----------------------------|-----------------|
| Ply Rating                 | 8               |
| Section Width (mm)         | 315             |
| Overall Diameter (mm)      | 1275            |
| Static Loaded Radius (mm)  | 595             |
| Rolling Circumference (mm) | 3749            |
| SRI (mm)                   | 600             |
| Rim Rec                    | W 11            |
| Rim Alt                    | W 9 ; W 10      |
| ECE                        | E11-106R-003551 |
| TRA Code                   | R1              |

## Load capacity (Kg)

| km/h / bar | 2.30 |
|------------|------|
| 30         | 1550 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 13:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..