

TR 137 - Spécifications techniques



Description

TR 137 est le pneu le plus adapté de BKT pour toutes les opérations de récolte, car il fait preuve d'une excellente traction dans les champs même avec des charges élevés. Ce pneu est disponible en différentes versions: la version "aramid-belted", avec ceintures en aramide, offre une meilleure résistance aux perforations et une bonne protection contre tous les dommages caractéristiques de cette application; la version "HD" offre une résistance extraordinaire aux coupures et déchirures ainsi qu'un cycle de vie du pneu long.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Moissonneuse

Version	STANDARD
Type	TL
Tyre Size	24.5 - 32
LI/SS	159 A6

Dimensions International Standard

Ply Rating	12
Section Width (mm)	622
Overall Diameter (mm)	1805
Static Loaded Radius (mm)	807
Rolling Circumference (mm)	5343
SRI (mm)	825
Rim Rec	DW 21 B
Rim Alt	DW 20 B
ECE	E4-106R-002271
TRA Code	R1

Load capacity (Kg)

km/h / bar	1.70
30	4375

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 00:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..