

TR 171 - Spécifications techniques



Description

TR 171 est un pneu avec bande de roulement profonde adapté pour les tracteurs dans les travaux de la terre. Grâce à ses extraordinaires propriétés d'auto-nettoyage, ce pneu est idéal pour les terrains humides et mouillés. Développé avec un mélange spécial, TR 171 assure une excellente traction et une grande durabilité même dans les conditions les plus difficiles.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Tracteur

Version	STANDARD
Type	TT
Tyre Size	8.3 - 20
LI/SS	96 A6

Dimensions International Standard

Ply Rating	6
Section Width (mm)	210
Overall Diameter (mm)	900
Static Loaded Radius (mm)	423
Rolling Circumference (mm)	2704
Rim Rec	W 7
Rim Alt	W 6
ECE	E11-106R-003362
TRA Code	R1W+

Load capacity (Kg)

km/h / bar	2.40
30	710

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 16:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..