

## TR 173 - Spécifications techniques



### Description

TR 173 est un pneu pour tracteurs adapté pour les terrains humides et les rizières. Le dessin particulier de la bande de roulement offre de grandes qualités d'auto-nettoyage et minimise le compactage du sol grâce à la large zone de contact.

### UM

US Standard

### Construction

BIAS

### Machinery

Agriculture: Tracteur

Version	STANDARD
Type	TT
Tyre Size	9.5 - 24
LI/SS	102 A8

## Dimensions US Standard

Usa code	94066988
Ply Rating	6
Section Width (inch)	9.5
Overall Diameter (inch)	41.2
Static Loaded Radius (inch)	19.4
Rolling Circumference (inch)	127.5
Rim Rec	W 8
Rim Alt	W 7
ECE	E11-106R-006486
TRA Code	R1W

## Load capacity (lbs)

	mph / psi	30
	25	1870

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 22:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..