

TR 270 - Spécifications techniques



Description

TR 270 est un pneu pour tracteurs adapté pour les applications de travail de la terre. Ce pneu a été spécialement conçu pour offrir un maximum de performances sur les terrains humides et mouillés. Dans ces conditions de sol, un pneu doit offrir une adhérence supérieure et des propriétés élevées d'auto-nettoyage. TR 270 satisfait parfaitement à ces requêtes.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Tracteur

Version	STANDARD
Type	TT
Tyre Size	13.6 - 46
LI/SS	122 A8

Dimensions US Standard

Usa code	94050826
Ply Rating	6
Section Width (inch)	13.6
Overall Diameter (inch)	71
Rim Rec	W12
Rim Alt	W12A
ECE	E11-106R-004343
TRA Code	R2

Load capacity (lbs)

	mph / psi	22
	25	3300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 01:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..