

TR 270 - Spécifications techniques



Description

TR 270 est un pneu pour tracteurs adapté pour les applications de travail de la terre. Ce pneu a été spécialement conçu pour offrir un maximum de performances sur les terrains humides et mouillés. Dans ces conditions de sol, un pneu doit offrir une adhérence supérieure et des propriétés élevées d'auto-nettoyage. TR 270 satisfait parfaitement à ces requêtes.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Tracteur

Version	STANDARD
Type	TT
Tyre Size	23.1 - 30
LI/SS	151 A8

Dimensions US Standard

Usa code	94026500
Ply Rating	12
Section Width (inch)	23.2
Overall Diameter (inch)	68.8
Static Loaded Radius (inch)	31.1
Rolling Circumference (inch)	205.8
Rim Rec	DW 20 A ; DW 20 B
ECE	E11-106R-004504
TRA Code	R2

Load capacity (lbs)

mph / psi	24
25	7600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 01:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..