

## TR 387 IND - Spécifications techniques



### Description

TR 387 IND est un pneu industriel, adapté pour les remorques industrielles et les compacteurs. Ce pneu se distingue par une capacité de charge élevée, et il est disponible en différentes versions afin de répondre aux exigences spécifiques des utilisateurs en termes de résistance aux coupures et déchirures, opérations de service pénible et durabilité. La version "dual bead", à double bourrelet, est particulièrement adaptée pour les tracteurs industriels et les opérations de transport avec remorques.

### UM

International Standard

### Construction

❖ BIAS

### Machinery

Industriel: Compacteur • Tracteur • Remorque

Version	DUAL BEAD HD
Type	TL
Tyre Size	24.5 - 32
LI/SS	164 A6

## Dimensions International Standard

Ply Rating	16
Section Width (mm)	625
Overall Diameter (mm)	1755
Static Loaded Radius (mm)	790
Rolling Circumference (mm)	5226
Rim Rec	DH 21
Rim Alt	DH 21 B ; DH 21 H ; DH 21 HB
TRA Code	R3

## Load capacity (Kg)

km/h / bar	2.10
30	5000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/02/2025 08:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..