

TR 459 - Spécifications techniques



Description

TR 459 a été spécialement conçu pour les opérations d'excavation et de chargement ainsi que pour les applications dans le secteur d'entretien de la voirie avec tracteurs et chargeuses-pelleteuses. Ce pneu offre une grande stabilité et il est disponible en deux versions. La version « spéciale » garantit une durée de vie prolongée du pneu.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Chargeuse-pelleteuse • Tracteur
Industriel: Chargeuse-pelleteuse

Version	INDUSTRIAL
Type	TL
Tyre Size	16.9 - 28
LI/SS	148 A8

Dimensions US Standard

Usa code	94016532
Ply Rating	10
Section Width (inch)	17.3
Overall Diameter (inch)	55.5
Static Loaded Radius (inch)	25.2
Rolling Circumference (inch)	163.2
Rim Rec	DW 15 L
Rim Alt	DW 14 L
ECE	E11-106R-005451
TRA Code	R4

Load capacity (lbs)

	mph / psi	32
	25	6950

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 00:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..