

TR 461 - Spécifications techniques



Description

TR 461 est un pneu BKT conçu per les applications entretien de la voirie avec tracteurs et pour les opérations de chargement avec chargeurs télescopiques. La protection du flanc est caractérisée par une résistance particulière aux coupures et lacérations, ce qui garantit une vie plus longue du pneu même sur des surfaces dures, ainsi qu'une excellente stabilité.

UM

International Standard

Construction

 BIAS

Machinery

Industriel: Chargeuse-pelleteuse • Chargeuse télescopique
• Tracteur

Version	HD
Type	TL
Tyre Size	620/60 B 34
LI/SS	175 A8

Dimensions International Standard

Overall Width (mm)	615
Overall Diameter (mm)	1629
Static Loaded Radius (mm)	750
Rolling Circumference (mm)	4930
Rim Rec	DW 20 B
TRA Code	R4

Load capacity (Kg)

km/h / bar	4.00
40	6900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 22:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..