

## TR 678 - Spécifications techniques



### Description

TR 678 a été particulièrement conçu pour les applications forestières. Le dessin robuste des crampons garantit d'excellentes qualités de traction et autonettoyage. La structure résistante de la carcasse permet une capacité de charge élevée, tandis que les ceintures d'acier protègent le pneu des dommages et crevaisons. TR 678 est caractérisé par un mélange résistant aux coupures qui garantit, même sur des terrains difficiles dans des conditions extrêmes, une excellente résistance aux coupures et lacérations.

### UM

US Standard

### Construction

❖ BIAS

### Machinery

Agriculture: Outillage agricole • Remorque  
Industriel: Pelleteuse • Remorque

Version	STEEL BELTED
Type	TL
Tyre Size	710/45 - 26.5
LI/SS	180 A2 / 173 A8

## Dimensions US Standard

Usa code	94075737
Ply Rating	24
Section Width (inch)	27.8
Overall Diameter (inch)	53
Rim Rec	AG 24.00
ECE	E11-106R-008292
TRA Code	LS2

## Load capacity (lbs)

mph / psi	87
25	14330
5	17640

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/02/2025 17:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..