

TRAC FARM - Spécifications techniques



Description

TRAC FARM est un pneu pour les opérations de service pénible spécialement conçu pour les tracteurs et les applications de travail de la terre et de transport. La bande de roulement profonde et le mélange spécial résistant aux coupures et déchirures rendent ce pneu adapté aux conditions opérationnelles les plus difficiles, ce qui garantit le meilleur rendement sur l'investissement pendant tout le cycle de vie du produit. TRAC FARM a été conçu avec un nombre plus élevé de pavés pour assurer une traction et des propriétés d'auto-nettoyage extraordinaires.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Tracteur

Version	STANDARD
Type	TT
Tyre Size	11.2 - 20
LI/SS	107 A8

Dimensions US Standard

Usa code	94043415
Ply Rating	8
Section Width (inch)	11.4
Overall Diameter (inch)	39.4
Static Loaded Radius (inch)	18.2
Rolling Circumference (inch)	115.7
Rim Rec	W 10
Rim Alt	W 9
ECE	E11-106R-003561
TRA Code	R1

Load capacity (lbs)

mph / psi	36
25	2150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 12:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..