

TRAC SUPER - Fiche de données



Description

Le pneu TRAC SUPER est la première taille radiale introduite par BKT dans le segment municipalité. La structure du pneu avec des ceintures en acier garantit une conduite stable associée à d'excellentes qualités de traction. Par conséquent il est tout particulièrement adapté aux applications sur les grandes surfaces herbeuses telles que les parcs et les bords de route.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Micro tracteur

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
400/50 R 15	STANDARD	94075300	118 A8	13.00		15	30.5	13	89.3	TL	E11-106R-009073
440/50 R 17	STANDARD	94038534	135 D	14.00	13.00	17.4	34.3	15.6	105.3	TL	E4-106R-000662
500/50 R 17	STANDARD	94073337	147 D	16.00		19.3	37	16.7	112.2	TL	E11-106R-007767

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 22:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..