

V-FLEXA - Spécifications techniques



Description

V-FLEXA est un pneu radial spécialement conçu pour les remorques agricoles. C'est un produit Flotation de dernière génération doté de la technologie VF, qui permet de transporter des charges lourdes tant aux champs que sur la route avec une pression de gonflage inférieure de 30% par rapport à celle d'un pneu standard de même taille. Des ceintures en acier confèrent à la carcasse une plus grande résistance aux agressions. V-FLEXA non seulement supporte des charges lourdes en toute sécurité, mais il évite aussi le compactage du sol grâce à la parfaite répartition du poids. De plus, V-FLEXA a d'excellentes propriétés d'auto-nettoyage, une longue durabilité et une faible résistance au roulement.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Remorque

Version	STEEL BELTED
Type	TL
Tyre Size	VF 560/60 R 22.5
LI/SS	166 D

Dimensions US Standard

Usa code	94066629
Section Width (inch)	21.9
Overall Diameter (inch)	49.2
Static Loaded Radius (inch)	21.7
Rolling Circumference (inch)	147.9
Rim Rec	AG 16.00
ECE	E11-106R-006763

Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46
45	4580	5860	7030	8100	8620	9790	10640
40	5030	6430	7720	8890	9470	10760	11690
30	5890	7530	9040	10410	11090	12590	13680
25	6500	8300	9960	11470	12230	13880	15080
5	8250	10550	12660	14580	15440	17640	19170

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 12:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..