

## XL GRIP (ADT) - Fiche de données



### Description

Le XL GRIP (ADT) est un pneu à carcasse radiale pour camions à benne articulés conçus pour minimiser les coupures et les perforations dans des conditions particulièrement difficiles exigeant une traction exceptionnelle. Ces caractéristiques se traduisent par une durée de vie prolongée des pneus.

### UM

US Standard

### Construction

 BIAS

### Machinery

OTR: Tombereau articulé

SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
26.5 - 25	STANDARD	94057870	E3	32	22.00/3.0		26.8	68.5	31.3	202.8	TL
26.5 - 25	STANDARD	94057863	E3	28	22.00/3.0		26.8	68.5	31.3	202.8	TL
29.5 - 25	STANDARD	94057887	E3	28	25.00/3.5		29.9	73.2	33.4	218.3	TL
29.5 - 25	STANDARD	94057894	E3	32	25.00/3.5		29.9	73.2	33.4	218.3	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 12:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..