

## XL GRIP PLUS - Fiche de données



### Description

XL GRIP PLUS (L-4) a été spécialement conçu pour les chargeuses. La bande de roulement profonde assure une excellente résistance aux coupures et crevaisons ainsi qu'un cycle de vie plus long du pneu. XL GRIP PLUS convient tout particulièrement pour les opérations de service pénible.

### UM

International Standard

### Construction

 BIAS

### Machinery

OTR: Bulldozer • Chargeur

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
26.5 - 25	STANDARD	L4	28	22.00/3.0		690	1775	815	5253	TL
26.5 - 25	STANDARD	L4	32	22.00/3.0		690	1775	815	5253	TL
29.5 - 25	STANDARD	L4	28	25.00/3.5		760	1915	876	5709	TL
29.5 - 25	STANDARD	L4	32	25.00/3.5		760	1915	876	5709	TL
29.5 - 25	STANDARD	L4	36	25.00/3.5		760	1915	876	5709	TL
35/65 - 33	STANDARD	L4	42	28.00/3.5		900	2080	0	0	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28/09/2024 05:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..