

AGRI TRAILER - Scheda tecnica



Description

AGRI TRAILER è stato specificamente sviluppato per rimorchi del trattore. Lo pneumatico è ideale per l'agricoltura moderna, essendo idoneo per di trasporto sia su strada che fuori strada. La sua costruzione robusta si traduce in elevata capacità di carico, mentre il battistrada extra profondo consente un migliore chilometraggio nonché un ciclo di vita prolungato dello pneumatico.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Rimorchio

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	Type
10.00 - 20	STANDARD	18	7.5	7.0 ; 8.0	286	1080	TT

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 05:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..