

## AGRIMAX RT 657 - Specifiche tecniche



### Description

AGRIMAX RT 657 è lo pneumatico ideale per la lavorazione del terreno e per l'utilizzo sulla strada; alcune misure sono anche idonee per la vendemmia. Lo pneumatico assicura un eccellente comfort di guida nonché risparmi significativi di carburante. Agrimax RT 657 è la scelta migliore per chi ha bisogno di uno pneumatico versatile e affidabile senza compromettere le performance.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricoltura: Trattore • Vendemmiatrice

|           |              |
|-----------|--------------|
| Version   | STANDARD     |
| Type      | TL           |
| Tyre Size | 420/65 R 24  |
| LI/SS     | 138 D/141 A8 |

## Dimensions US Standard

|                              |                |
|------------------------------|----------------|
| Usa code                     | 94042562       |
| Section Width (inch)         | 16.5           |
| Overall Diameter (inch)      | 45.5           |
| Static Loaded Radius (inch)  | 20.4           |
| Rolling Circumference (inch) | 136.5          |
| Rim Rec                      | W 13           |
| Rim Alt                      | W 11 ; W 12    |
| ECE                          | E4-106R-000761 |
| TRA Code                     | R1W            |

## Load capacity (lbs)

| mph / psi | 9    | 12   | 15   | 17   | 20   | 23   | 29   | 35   |
|-----------|------|------|------|------|------|------|------|------|
| 40        | 2450 | 2870 | 3280 | 3650 | 4010 | 4320 | 4790 | 5200 |
| 30        | 2580 | 3010 | 3450 | 3840 | 4210 | 4540 | 5040 | 5470 |
| 25        | 2680 | 3130 | 3580 | 3980 | 4380 | 4720 | 5220 | 5680 |
| 20        | 2820 | 3300 | 3780 | 4200 | 4620 | 4970 | 5510 | 5990 |
| 5 LT      | 3280 | 3850 | 4400 | 4890 | 5380 | 5800 | 6430 | 6980 |
| 5 HT      | 2820 | 3300 | 3780 | 4200 | 4620 | 4970 | 5510 | 5990 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 22:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..