

AGRIMAX RT 855 - Specifiche tecniche



Description

AGRIMAX RT 855 si distingue per l'eccellente trazione e il comfort. Principalmente sviluppato per la lavorazione del terreno e il trasporto sia su campo che sulla strada, alcune misure sono anche idonee per applicazioni di irrorazione e vendemmia. AGRIMAX RT 855 possiede ottime doti di autopulitura che consentono il rapido cambio dalle operazioni sul campo all'impiego su strada.

UM

US Standard

Construction

 RADIAL

Machinery

Agricoltura: Macchina irroratrice • Trattore • Vendemmiatrice

Version	SPECIAL
Type	TL
Tyre Size	320/85 R 34 (12.4 R 34)
LI/SS	141 A8/B

Dimensions US Standard

Usa code	94047239
Section Width (inch)	13
Overall Diameter (inch)	55.4
Static Loaded Radius (inch)	25.4
Rolling Circumference (inch)	168.5
Rim Rec	W 11
Rim Alt	W 9 ; W 10
ECE	E4-106R-000758
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	17	23	29	35	41	46	52
30	2050	2390	3130	3810	4140	4430	4830	5220	5680
25	2050	2390	3130	3810	4140	4430	4830	5220	5680
20	2190	2560	3350	4080	4440	4750	5180	5600	6080
5 LT	2740	3210	4200	5100	5570	5940	6480	7010	7620
5 HT	2190	2560	3350	4080	4440	4750	5180	5600	6080

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 05:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..